

承認書

SPECIFICATION FOR APPROVAL

CUSTOMER: _____

DESCRIPTION: WIRE WOUND CHIP INDUCTOR

Cybermax PART NO: CMCW1005FR56KST

CUSTOMERMODELNO: _____

DRAWING			CUSTOMER APPROVE
MADE	CHECKED	APPROVED	
曹春宁	张有涛	陈启善	
DATE:	2019年07月08日		



CUSTOMER:		REV NO:	A1.0
DESCRIPTION:	WIRE WOUND CHIP INDUCTOR	PAGE NO:	PAGE 1 OF 6
PART NO:	CMCW1005FR56KST	SN.	
CUSTOMER NO:		DATE:	2019年07月08日

变更履历

日期	版本	修订内容	制定	核准
2019-07-08	A1.0	新版发行	曹春宁	陈启善

CUSTOMER:		REV NO:	A1.0
DESCRIPTION:	WIRE WOUND CHIP INDUCTOR	PAGE NO:	PAGE 2 OF 6
PART NO:	CMCW1005FR56KST	SN.	
CUSTOMER NO:		DATE:	2019年07月08日

UNIT:mm



CODE	L	W	T	E	F	D	
DIMENSION	1.19MAX	0.66MAX	0.64MAX	0.40Typ.	0.64Typ.	0.64Typ.	

2. ELECTRICAL CHARACTERISTICS @25°C

ITEM	SPEC. RANGE	TEST CONDITION	TEST INSTRUMENTS
L(nH)	560±10%	7.9MHz/0.5V	HP4286A
DCR(Ω)	1.2 MAX		502BC
I _{rms} (mA)	200 MAX		VR116+VR7210
SRF	600 MIN		E5071C ENA

3. PART NUMBERING SYSTEM


CMCW □□□□ □□ □R□ □ □ □
 2 3 4 5 6 7

- 1 PRODUCT SYMBOL (产品代号)
- 2 DIMENSIONS (规格尺寸)
- 3 MATERIAL (芯片类型)
- 4 INDUCTANCE (电感量)
- 5 TOLERANCE (公差) : F±1%; G±2%; J±5%; K±10%; M±20%
- 6 TERMINAL (端电极材料) : G-金端头; S-锡端头; Y-银钯端头
- 7 PACKAGING (包装方式) : T-编带盘装; B-散装

APPROVED BY	CHECKED BY	DRAFT
陈启善	张有涛	曹春宁

CUSTOMER:					REV NO:	A1.0	
DESCRIPTION:		WIRE WOUND CHIP INDUCTOR			PAGE NO:	PAGE 3 OF 6	
PART NO:		CMCW1005FR56KST			SN.		
CUSTOMER NO:					DATE:	2019年07月08日	
TEST	L	DCR		L	W	T	
ITEM	(nH)	(Ω)		(mm)	(mm)	(mm)	
CON.	7.9MHz/0.5V	At 25°C		1.19MAX	0.66MAX	0.64MAX	
SPEC.	560±10%	1.20 MAX					
1	561.29	0.92		1.07	0.64	0.56	
2	559.97	0.93		1.08	0.63	0.55	
3	558.96	0.92		1.09	0.62	0.56	
4	561.13	0.93		1.08	0.63	0.54	
5	560.37	0.92		1.07	0.64	0.55	
6	559.86	0.94		1.09	0.62	0.56	
7	560.26	0.92		1.08	0.64	0.54	
8	560.26	0.93		1.07	0.63	0.55	
9	559.89	0.93		1.09	0.64	0.56	
10	559.96	0.93		1.08	0.63	0.54	
X	560.2	1.55		1.08	0.63	0.55	
R	2.33	0.03		0.02	0.02	0.02	

图示:




APPROVED BY	CHECKED BY	DRAFT
陈启善	张有涛	曹春宁

CUSTOMER:		REV NO:	A1.0
-----------	--	---------	------

DESCRIPTION:	WIRE WOUND CHIP INDUCTOR	PAGE NO:	PAGE 4 OF 6
PART NO:	CMCW1005FR56KST	SN:	
CUSTOMER NO:		DATE:	2019年07月08日


**Figure 1.
Re-flow
Soldering (Lead
Free)**



Note:

- Preheat circuit and products to 150°C
- 280°C tip temperature (max)


**Figure 2.
Wave Soldering**



Note :

- Never contact the ceramic with the iron tip
- 1.0mm tip diameter (max)

**Figure 3.
Hand Soldering**



Note:

- Use a 20 watt soldering iron with tip diameter of 1.0mm
- Limit soldering time to 3 sec.



APPROVED BY	CHECKED BY	DRAWN BY
陈启善	张有涛	曹春宁

CUSTOMER:		REV NO:	A1.0
-----------	--	---------	------


DESCRIPTION:	WIRE WOUND CHIP INDUCTOR	PAGE NO:	PAGE 5 OF 6
PART NO:	CMCW1005FR56KST	SN:	
CUSTOMER NO:		DATE:	2019年07月08日

Tape


POLYSTYRENE TAPE



Reel Dimensions



PAPER TAPE



unit:(mm)

		A	B	T
纸带	0402	0.74	1.23	0.60
	0603	1.15	1.83	0.95
	0805	1.85	2.40	1.45
胶带	1008	2.73	2.90	2.34
	1210	2.96	3.60	2.40
	1812	3.22	4.82	3.15

unit	ΦA	ΦB	ΦC	ΦD	E	W	t	R
mm	178	60	13	21	2	10	2	1
	330	75	13	23	2	12	2	1


包装数量

Packaging Quantity

规格 Dimension	0402	0603	0805	1008	1210	1812
数量 Quantity(pcs)	10000	4000	3000	2000	2000	2000

APPROVED BY	CHECKED BY	DRAFT
陈启善	张有涛	曹春宁

CUSTOMER:	REV NO:	A1.0
-----------	---------	------

DESCRIPTION:	WIRE WOUND CHIP INDUCTOR	PAGE NO:	PAGE 6 OF 6
PART NO:	CMCW1005FR56KST	SN:	
CUSTOMER NO:		DATE:	2019年07月08日
High Temperature Storage	No evidence of mechanical damage Inductance change, less than $\pm 5\%$ Q change less than $\pm 10\%$	Test Temperature: $125 \pm 2^\circ\text{C}$ (Ceramic core) $85 \pm 2^\circ\text{C}$ (Ferrite core) Test Time: 96 ± 2 Hours	
Low Temperature Storage	No evidence of mechanical damage Inductance change, less than $\pm 5\%$ Q change less than $\pm 10\%$	Test Temperature: $-40 \pm 2^\circ\text{C}$ Test Time: 96 ± 2 Hours	
Moisture Resistance	No evidence of mechanical damage Inductance change, less than $\pm 5\%$ Q change less than $\pm 10\%$	Test Temperature: $50 \pm 2^\circ\text{C}$ Test Time: 100 Hours 相对湿度 90~95%	
Vibration	No evidence of mechanical damage Inductance change, less than $\pm 5\%$ Q change less than $\pm 10\%$	Amplitude: 1.5mm X、Y、Z方向各 1Hours45min Frequency range: 10~55~10Hz(min)	
Component Adhesion	No evidence of mechanical damage No evidence of peel off or broken Keep continuity of Winding	Force: 2Kgf Test Time: 5 ± 1 秒	
Resistance to bend	No evidence of mechanical damage	Camber: 20mm Test Board: Glass-Epoxy board Thickness: 8mm 	
Life	No evidence of mechanical damage Inductance change, less than $\pm 5\%$ Q change less than $\pm 10\%$	Test Temperature: $85 \pm 2^\circ\text{C}$ Test Time: 1000 Hours with rating current Test Time: 96 ± 2 Hours	
APPROVED BY	CHECKED BY	DRAFT	
陈启善	张有涛	曹春宁	