

## Low Capacitance TVS Protection

### ◆ DESCRIPTIONS

CMTLDF02C350BFE is a low-capacitance Transient Voltage Suppressor (TVS) designed to provide electrostatic discharge (ESD) protection for high-speed data interfaces. With typical capacitance of 35pF only, CMTLDF02C350BFE is designed to protect parasitic-sensitive systems against over-voltage and over-current transient events. It complies with IEC 61000-4-2(ESD), Level 4 ( $\pm 15\text{kV}$  air,  $\pm 8\text{kV}$  contact discharge), IEC 61000-4-4 (electrical fast transient - EFT) (40A, 5/50 ns), very fast charged device model (CDM) ESD and cable discharge event (CDE), etc.

CMTLDF02C350BFE uses ultra-small uDFN-2L package. Each CMTLDF02C350BFE device can protect one data line. It offers system designers flexibility to protect single data line where space is a premium concern.


### ◆ FEATURES

- 1、Transient protection for high-speed data lines  
IEC 61000-4-2 (ESD)  $\pm 15\text{kV}$  (Air)  
 $\pm 8\text{kV}$  (Contact)  
IEC 61000-4-4 (EFT) 40A (5/50 ns)  
Cable Discharge Event (CDE)
- 2、Package optimized for high-speed lines
- 3、Ultra-small package (1.0mm  $\times$  0.6mm  $\times$  0.55mm)
- 4、Protects one data, control or power line
- 5、Low capacitance: 35pF (Typical)
- 6、Low leakage current: 0.1  $\mu\text{A}$  @  $V_{\text{RWM}}$  (Typical)
- 7、Low clamping voltage
- 8、Each I/O pin can withstand over 1000 ESD strikes for  $\pm 8\text{kV}$  contact discharge

### ◆ Circuit Diagram



### ◆ Pin Configuration



### ◆ Applications

- 1、Portable Electronics
- 2、Desktops, Servers and Notebooks
- 3、Cellular Phones
- 4、MP3 Ports
- 5、Digital Camera Ports
- 6、Audio and Video Equipment

### ◆ Mechanical Characteristics


- 1、uDFN-2L package
- 2、Flammability Rating: UL 94V-0
- 3、Marking: Part number, date code
- 4、Packaging: Tape and Reel

◆ **Absolute Maximum Rating**

Symbol	Parameter	Value	Units
$I_{PP}$	Peak Pulse Current (8/20 $\mu$ s)	12	A
$P_{PK}$	Peak Pulse Power (8/20 $\mu$ s)	130	W
$V_{ESD}$	ESD per IEC 61000-4-2 (Air) ESD per IEC 61000-4-2 (Contact)	$\pm 30$ $\pm 30$	kV
$T_{OPT}$	Operating Temperature	-55/+125	$^{\circ}$ C
$T_{STG}$	Storage Temperature	-55/+150	$^{\circ}$ C

◆ **Electrical Characteristics (T = 25 $^{\circ}$ C)**


Symbol	Parameter
$V_{RWM}$	Nominal Reverse Working Voltage
$I_R$	Reverse Leakage Current @ $V_{RWM}$
$V_{BR}$	Reverse Breakdown Voltage @ $I_T$
$I_T$	Test Current for Reverse Breakdown
$V_C$	Clamping Voltage @ $I_{PP}$
$I_{PP}$	Peak Pulse Current
$C_{ESD}$	Parasitic Capacitance
$V_R$	Reverse Voltage
f	Small Signal Frequency




Symbol	Test Condition	Minimum	Typical	Maximum	Units
$V_{RWM}$		-	-	5.0	V
$I_R$	$V_{RWM} = 5V, T = 25^{\circ}C$ Between I/O and I/O	-	0.1	1.0	$\mu$ A
$V_{BR}$	$I_T = 1mA$ Between I/O and I/O	6.0	7.0	9.0	V
$V_C$	$I_{PP} = 1A, t_p = 8/20\mu s$ Between I/O and I/O	-	-	10	V
$V_C$	$I_{PP} = 2A, t_p = 8/20\mu s$ Between I/O and I/O	-	-	14	V
$C_{ESD}$	$V_R = 0V, f = 1MHz$ Between I/O and I/O	-	35	45	pF

◆ **TYPICAL ELECTRICAL CHARACTERISTICS CURVE**

**TLP Measurement of I/O\_1 to I/O\_2**




**Voltage Sweeping of I/O\_1 to I/O\_2**




**Capacitance vs. Voltage of I/O\_1 to I/O\_2 (f = 1MHz)**


Capacitance vs. Reverse Voltage




Normalized Capacitance vs. Reverse Voltage



**ESD Clamping of I/O\_1 to I/O\_2 (+8kV Contact per IEC 61000-4-2)**




**ESD Clamping of I/O\_1 to I/O\_2 (-8kV Contact per IEC 61000-4-2)**



◆ **PACKAGE OUTLINE**

- 1、uDFN-2L package
- 2、2 leads, very small package
- 3、MSL - 1



Package Dimensions (Controlling dimensions are in millimeters)

Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Minimum	Maximum	Minimum	Maximum
A	0.400	0.550	0.016	0.022
A1	0.000	0.050	0.000	0.002
A3	0.125 REF		0.005 REF	
D	0.950	1.050	0.037	0.041
E	0.550	0.650	0.022	0.026
b	0.200	0.300	0.008	0.012
e	0.650 BSC		0.026 BSC	
L	0.450	0.550	0.018	0.022