

Low Capacitance TVS Protection

◆ **DESCRIPTIONS**

CMTLDF0603C150BFE is a low-capacitance Transient Voltage Suppressor (TVS) designed to provide electrostatic discharge (ESD) protection for high-speed data interfaces. With minimum capacitance of 10pF only, CMTLDF0603C150BFE is designed to protect parasitic-sensitive systems against over-voltage and over-current transient events. It complies with IEC 61000-4-2 (ESD), Level 4 ($\pm 15\text{kV}$ air, $\pm 8\text{kV}$ contact discharge), IEC 61000-4-4 (electrical fast transient - EFT) (40A, 5/50 ns), very fast charged device model (CDM) ESD and cable discharge event (CDE), etc.

CMTLDF0603C150BFE uses ultra-small DFN0603 package. Each CMTLDF0603C150BFE device can protect one data line. It offers system designers flexibility to protect single data line where space is a premium concern.


◆ **FEATURES**

- 1、Transient protection for high-speed data lines
IEC 61000-4-2 (ESD) $\pm 15\text{kV}$ (Air)
 $\pm 8\text{kV}$ (Contact)
IEC 61000-4-4 (EFT) 40A (5/50 ns)
Cable Discharge Event (CDE)
- 2、Package optimized for high-speed lines
- 3、Ultra-small package ($0.6\text{mm} \times 0.3\text{mm} \times 0.3\text{mm}$)
- 4、Protects one data, control or power line
- 5、Low capacitance: 15pF (Typical)
- 6、Low leakage current: $0.1\mu\text{A}$ @ VRWM (Typical)
- 7、Low clamping voltage
- 8、Each I/O pin can withstand over 1000 ESD strikes for $\pm 8\text{kV}$ contact discharge

◆ **Circuit Diagram**



◆ **Pin Configuration**



◆ **Applications**

- 1、Portable Electronics
- 2、Desktops, Servers and Notebooks
- 3、Cellular Phones
- 4、MP3 Ports
- 5、Digital Camera Ports
- 6、Display Ports

◆ **Mechanical Characteristics**


- 1、DFN0603 package
- 2、Flammability Rating: UL 94V-0
- 3、Marking: Part number
- 4、Packaging: Tape and Reel

◆ **Absolute Maximum Rating**

Symbol	Parameter	Value	Units
V_{ESD}	ESD per IEC 61000-4-2 (Air)	± 30	kV
	ESD per IEC 61000-4-2 (Contact)	± 30	
T_{OPT}	Operating Temperature	-55/+125	$^{\circ}\text{C}$
T_{STG}	Storage Temperature	-55/+150	$^{\circ}\text{C}$

◆ **Electrical Characteristics ($T = 25^{\circ}\text{C}$)**


Symbol	Parameter
V_{RWM}	Nominal Reverse Working Voltage
I_R	Reverse Leakage Current @ V_{RWM}
V_{BR}	Reverse Breakdown Voltage @ I_T
I_T	Test Current for Reverse Breakdown
V_C	Clamping Voltage @ I_{PP}
I_{PP}	Peak Pulse Current
C_{ESD}	Parasitic Capacitance
V_R	Reverse Voltage
f	Small Signal Frequency




Symbol	Test Condition	Minimum	Typical	Maximum	Units
V_{RWM}				5.0	V
I_R	$V_{RWM} = 5\text{V}$, $T = 25^{\circ}\text{C}$ Between I/O and I/O		0.1	1.0	μA
V_{BR}	$I_T = 1\text{mA}$ Between I/O and I/O	5.5	6.0	8.0	V
V_C	$I_{PP} = 1\text{A}$, $t_p = 8/20\mu\text{s}$ Between I/O and I/O			10	V
V_C	$I_{PP} = 2\text{A}$, $t_p = 8/20\mu\text{s}$ Between I/O and I/O			15	V
C_{ESD}	$V_R = 0\text{V}$, $f = 1\text{MHz}$ Between I/O and I/O	10	15	18	pF

◆ TYPICAL ELECTRICAL CHARACTERISTICS CURVE

TLP Measurement of I/O_1 to I/O_2




Voltage Sweeping of I/O_1 to I/O_2




Capacitance vs. Voltage of I/O_1 to I/O_2 (f = 1MHz)


Capacitance vs. Reverse Voltage




Normalized Capacitance vs. Reverse Voltage



**ESD Clamping of I/O_1 to I/O_2
(+8kV Contact per IEC 61000-4-2)**




**ESD Clamping of I/O_1 to I/O_2
(-8kV Contact per IEC 61000-4-2)**



◆ **PACKAGE OUTLINE**

- 1、DFN0603 package
- 2、2 Leads
- 3、MSL - 1



Package Dimensions (Controlling dimensions are in millimeters)

Symbol	Dimensions (mm)			Dimensions (Inches)		
	Minimum	Typical	Maximum	Minimum	Typical	Maximum
A	0.280	0.300	0.320	0.011	0.012	0.013
b	0.220	—	0.280	0.009	—	0.011
D	0.275	0.300	0.325	0.011	0.012	0.013
E	0.575	0.600	0.625	0.023	0.024	0.025
e	—	0.380	—	—	0.015	—
L	0.140	—	0.200	0.005	—	0.008