


Ultra-Low Capacitance TVS Protection

◆ DESCRIPTIONS


CMTLDF0603C6R0BFE is a low-capacitance Transient Voltage Suppressor (TVS) designed to provide electrostatic discharge (ESD) protection for high-speed data interfaces. With typical capacitance of 6pF only, CMTLDF0603C6R0BFE is designed to protect parasitic-sensitive systems against over-voltage and over-current transient events. It complies with IEC 61000-4-2 (ESD), Level 4 ($\pm 15\text{kV}$ air, $\pm 8\text{kV}$ contact discharge), IEC 61000-4-4 (electrical fast transient - EFT) (40A, 5/50 ns), very fast charged device model (CDM) ESD and cable discharge event (CDE), etc.

CMTLDF0603C6R0BFE uses ultra-small DFN0603 package. Each CMTLDF0603C6R0BFE device can protect one high-speed data line. It offers system designers flexibility to protect single data line where space is a premium concern.

◆ Circuit Diagram



◆ Pin Configuration



◆ FEATURES

1. Transient protection for high-speed data lines
IEC 61000-4-2 (ESD) $\pm 30\text{kV}$ (Air)
 $\pm 30\text{kV}$ (Contact)
- IEC 61000-4-4 (EFT) 40A (5/50 ns)
Cable Discharge Event (CDE)
2. Package optimized for high-speed lines
3. Ultra-small package (0.6mm×0.3mm×0.3mm)
4. Protects one data, control or power line
5. Low capacitance: 6pF (Typical)
6. Low leakage current: 0.1uA@ VRWM (Typical)
7. Low clamping voltage
8. Each I/O pin can withstand over 1000 ESD strikes
for $\pm 8\text{kV}$ contact discharge

◆ Applications

1. Portable Electronics
2. Desktops, Servers and Notebooks
3. Cellular Phones
4. MP3 Ports
5. Digital Camera Ports

◆ Mechanical Characteristics


1. DFN0603 package
2. Flammability Rating: UL 94V-0
3. Packaging: Tape and Reel
4. Reel size: 7 inch

◆ Absolute Maximum Rating

Symbol	Parameter	Value	Units
V_{ESD}	ESD per IEC 61000-4-2 (Air) ESD per IEC 61000-4-2 (Contact)	± 30 ± 30	kV
T_{OPT}	Operating Temperature	-55/+125	°C
T_{STG}	Storage Temperature	-55/+150	°C

◆ Electrical Characteristics ($T = 25^\circ\text{C}$)


Symbol	Parameter
V_{RWM}	Nominal Reverse Working Voltage
I_R	Reverse Leakage Current @ V_{RWM}
V_{BR}	Reverse Breakdown Voltage @ I_T
I_T	Test Current for Reverse Breakdown
V_C	Clamping Voltage @ I_{PP}
I_{PP}	Peak Pulse Current
C_{ESD}	Parasitic Capacitance
V_R	Reverse Voltage
f	Small Signal Frequency




Symbol	Test Condition	Minimum	Typical	Maximum	Units
V_{RWM}	Reverse Working Voltage				5.0
V_{BR}	Reverse Breakdown Voltage	$I_T = 1\text{mA}$	5.5	6.0	8.0
I_R	Reverse Leakage Current	$V_{RWM} = 5\text{V}$		0.1	1.0
V_{C1}	Clamping Voltage 1	$I_{PP} = 1\text{A},$ $t_p = 8/20\mu\text{s}$			10
V_{C2}	Clamping Voltage 2	$I_{PP} = 4\text{A},$ $t_p = 8/20\mu\text{s}$			15
C_J	Junction Capacitance	$V_R = 0\text{V},$ $f = 1\text{MHz}$	4	6	9

◆ TYPICAL ELECTRICAL CHARACTERISTICS CURVE

TLP Measurement of I/O_1 to I/O_2




Voltage Sweeping of I/O_1 to I/O_2




Capacitance vs. Voltage of I/O_1 to I/O_2 (f = 1MHz)


Capacitance vs. Reverse Voltage




Normalized Capacitance vs. Reverse Voltage



ESD Clamping of I/O_1 to I/O_2
(+8kV Contact per IEC 61000-4-2)




ESD Clamping of I/O_1 to I/O_2
(-8kV Contact per IEC 61000-4-2)



◆ PACKAGE OUTLINE

- 1、DFN0603 package
- 2、2 bumps, very small package
- 3、Thermally-Enhanced



Package Dimensions (Controlling dimensions are in millimeters)

Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Minimum	Maximum	Minimum	Maximum
A	0.240	0.300	0.009	0.012
A1	0.000	0.010	0.000	0.001
D	0.300 BSC		0.012 BSC	
E	0.600 BSC		0.024 BSC	
b	0.190	0.230	0.007	0.009
e	0.400 BSC		0.016 BSC	
L	0.100	0.140	0.004	0.006